

TouchChip[®] TCS2 Sensor

Silicon Fingerprint Sensor



PRODUCT DESCRIPTION

The TouchChip TCS2 fingerprint sensor offers a medium size capture area for a silicon fingerprint sensor, ensuring reliable biometric performance at a cost effective price. Combining the TCS2 with the Enhanced Image Mode (EIM) technology delivers an image quality comparable to the FIPS-201 certified TCS1 sensor. The SteelCoat protective technology enhances durability of the sensor while still enabling excellent biometric performance.

The TouchChip TCS2 sensor provides excellent fingerprint images across a wide range of users, making it a reliable solution for many identity verification applications. It is designed into many logical and physical access control products where the convenience of “touch” and budget are important.

FEATURES

- Most widely deployed silicon touch sensor technology
- Image quality comparable to the TCS1 sensor that is FIPS-201 certified
- Ideal for more cost sensitive touch applications
- Small size & low power

ABOUT CROSSMATCH[®]

Crossmatch helps organizations solve their identity management challenges through biometrics. Our enrollment and authentication solutions are trusted to create, validate and manage identities for a wide range of government, law enforcement, financial institution, retail and commercial applications. Our solutions are designed using proven biometric technologies, flexible enrollment and strong multi-factor authentication software, and deep industry expertise. We offer an experienced professional services capability to assess, design, implement and optimize our identity management solutions for a customer’s individual challenges. Our products and solutions are utilized by over 200 million people in more than 80 countries.

Learn more at www.crossmatch.com

TouchChip® TCS2 Sensor

Silicon Fingerprint Sensor



SPECIFICATIONS

Medium Capture Area	<ul style="list-style-type: none">• 10.4 x 14.4 mm imaging array size
High Resolution	<ul style="list-style-type: none">• 8-bit per pixel grayscale• Up to 12 frames per second capture rate
Interface	<ul style="list-style-type: none">• 8-bit RAM interface• 20-pin 0.5mm pitch flat flex cable connector
Low Power	<ul style="list-style-type: none">• 20mA during capture (typical)• 4.5v to 4.6v (EIM-lite mode w/bezel)
Durability	<ul style="list-style-type: none">• +/- 15 KV ESD (IEC 61000-4-2 level 4)• 4M fingerprint placements
Environment	<ul style="list-style-type: none">• -30 to +85C operating• -40 to +85 storage• RoHS compliant
<i>Data subject to change without notice</i>	

ADVANTAGES

- Active capacitance technology delivers excellent image quality and ability to acquire.
- Enhanced Image Mode (EIM-lite) optimizes image quality over broad range of skin types and capture conditions, plus eliminates latent images during capture.
- TouchChip SteelCoat coating improves ruggedness.

Corporate Headquarters:

Crossmatch

3950 RCA Boulevard, Suite 5001
Palm Beach Gardens, FL 33410 USA

www.crossmatch.com