

## CARGADORES

| Part No. | NSN              | Charges  | Dimensions (mm)<br>Thickness x Width x<br>Length | Charge<br>Termination<br>Voltage (V) | Max.<br>Charge Rate<br>(A) | Weight (g) |
|----------|------------------|----------|--|--------------------------------------|----------------------------|------------|
| CH0001   |                  | LWC-L    | 92 x 58 x 52                                     | 16.8                                 | 3.0                        | 170        |
| CH0002   |                  | UBI-2590 | 174 x 123.7 x 53.6                               | 16.8                                 | 1.0                        | 432        |
| CH0003   | 6130-01-499-7305 | UBI-2590 | 61 x 51 x 22 cm                                  | 16.4                                 | 1.1                        | 11 Kg      |
| CH0004   | 6130-01-499-0352 | UBI-2590 | 36 x 31 x 16 cm                                  | 16.4                                 | 1.1                        | 5 Kg       |
| CH0005   |                  | UBBL04   | 92 x 58 x 52                                     | 8.4                                  | 2.0                        | 170        |
| CH0006   |                  | UBBL06   | 31.62 x 14.02 x 28.50 cm                         | 16.8                                 | 8.0                        | 6.35 Kg    |
| CH0007   |                  | UBBL03   | 35.1 x 31.3 x 71.8 cm                            | 16.8                                 | 2.0                        | 16.7 Kg    |
| CH0008   | 6130-01-545-1983 | UBBL06   | 42 x 73 x 168                                    | 16.8                                 | 2.0                        | 1.7 Kg     |
| CH0012   | 6130-01-545-1981 | UBBL06   | 61.24 x 21.46 x 28.96 cm                         | 16.8                                 | 4.0                        | 17.24 Kg   |
| CH0014   |                  | UBBL09   | 124 x 175 x 50                                   | 12.6                                 | 2.0                        | 269        |
| CH0015   | 6130-01-542-5108 | UBBL06   | 92 x 58 x 52                                     | 16.8                                 | 3.0                        | 171        |

## Fuente de alimentación

| Part No. | NSN              | Charges       | Dimensions (mm)<br>Thickness x Width x<br>Length | Output<br>Voltage (V) | Max.<br>Output<br>Power (W) | Weight (g) |
|----------|------------------|---------------|--|-----------------------|-----------------------------|------------|
| CH0018   | 6130-01-545-1984 | CH0012 CH0017 | 7.0 x 14.0 x 19.0                                | 28 DC                 | 1500                        | 12         |

## Cables

| Part No. | Battery Type   | Length (cm) | Type                                  | Connector   | Voltage (V) |
|----------|--|-------------|---------------------------------------|-------------|-------------|
| CA0001   | LWC-L  | 61          | 2 Conductor; 22 AWG                   | Straight    | -           |
| CA0002   | UBI-2590,<br>UBBL09, UBI-2590<br>SMBus                             | 61          | 4 Conductor; 18 AWG                   | Straight    | 12/24       |
| CA0003   | UBI-2590   | 61          | Vehicle Adapter                       | Straight    | -           |
| CA0005   | UBBL03   | 61          | 5 Conductor; 20 AWG                   | Straight    | 12          |
| CA0006   | BA-5390/U, UBI-<br>2590, UBBL09, BA-<br>5390A/U, UBI-2590<br>SMBus | 61          | 2 Conductor; 18 AWG                   | Right Angle | 24          |
| CA0007   | BA-5390/U, UBI-<br>2590, UBBL09, BA-<br>5390A/U, UBI-2590<br>SMBus | 61          | 2 Conductor; 18 AWG                   | Right Angle | 12          |
| CA0008   | BA-5390/U, UBI-<br>2590, UBBL09, BA-<br>5390A/U, UBI-2590<br>SMBus | 61          | 4 Conductor; 18 AWG                   | Right Angle | 12/24       |
| CA0009   | UBBL06, UBBL08   | 61          | 6 Conductor; 22 AWG<br>(Non-shielded) | Straight    | -           |
| CA0022   | UBBL06, UBBL08   | 61          | 6 Conductor; 22 AWG<br>(Shielded)     | Straight    | -           |